

Steele Plastics, Inc

1280 Sturgis Rd., P. O. Box 1076
Conway Arkansas 72032
PH: (501)327-5122 FAX: (501)327-0807

Specifications

Single Door Steel Hatch Cover

SCOPE

This specification is intended to describe the minimum design and manufacturing requirements for Single Door Steel Hatch covers as manufactured by Steele Plastics Inc.

STYLE: Single Door Hatch Cover

SIZES: 30", 36", 42", 48" (as measured inside basin/wetwell diameter)

Material: A36 or equal

Thickness: ¼" minimum

Type: Hot Rolled Mill finish

-
- The cover shall be 6" larger in diameter than the wet well.
- The cover shall be reinforced to support a live load of 300 psf.
- The cover plate shall have a flush fitting access door, and raised steel handle.
- The door shall open to a minimum of 160 degrees and be removable.
- The hinges shall be steel and welded in place.
- The cover shall be equipped with a padlock provision.
- The cover shall be blank, have a vent grommet or a vent coupling as required to meet the application.
- The cover shall have 6ea ¾" diameter holes around the perimeter on a 60 degree bolt pattern for attaching to basin/wetwell.
- The cover shall be painted with polyurethane enamel paint.
- The cover can be painted with optional Coal Tar Epoxy Paint.
- The cover shall be supplied with Gaket and Stainless Steel bolts and washers for attachment to the basin/wetwell.
- The cover door is designed for maximum pump access, and can NOT be gasketed.

This cover shall be as manufactured by Steele Plastics Inc, Conway Arkansas.