



NOTES:

- COVER SHALL BE PAINTED WITH GREEN INDUSTRIAL GRADE POLYURETHANE ENAMEL OR OPTIONAL BLACK COAL TAR EPOXY.
- 300 PSF LOAD RATING.
- HATCH IS, DESIGNED FOR MAX PUMP ACCESS, SUPPORTED BY TWO STEEL ANGLE BRACES.
NOTE - CAN NOT BE MADE VAPOR TIGHT.

DIMENSIONAL DATA							
BASIN I.D.	"B"	Cover Thickness	"D"	"E"	"F"	"G"	"H"
30"	34"	1/4"	32 1/2"	24"	20"	18"	1 1/4", 1 1/2", 2", 3"
36"	40"	1/4"	38 1/2"	30"	22"	20"	1 1/4", 1 1/2", 2", 3"
42"	48"	1/4"	44 1/2"	36"	24"	22"	1 1/4", 1 1/2", 2", 3", 4"
48"	54"	1/4"	51"	40"	30"	28"	1 1/4", 1 1/2", 2", 3", 4"



STEELE PLASTICS, INC.
1280 Sturgis Rd.
Conway, AR 72034
(501) 327-5122 Fax (501) 327-0807

TITLE		SINGLE DOOR STEEL HATCH COVER	
PROJECT		JOB NO.	
		P.O. NO.	
CUSTOMER		DWG. NO.	CVSHTHSD