


NOTES:

1. COVER SHALL BE PAINTED WITH GREEN INDUSTRIAL GRADE POLYURETHANE ENAMEL OR OPTIONAL BLACK COAL TAR EPOXY.
2. 300 PSF LOAD RATING.
3. HATCH IS, DESIGNED FOR MAX PUMP ACCESS, SUPPORTED BY TWO STEEL ANGLE BRACES.
NOTE - CAN NOT BE MADE VAPOR TIGHT.

DIMENSIONAL DATA							
BASIN I.D.	"B"	Cover Thickness	"D"	"E"	"F"	"G"	"H"
30"	34"	1/4"	32 1/2"	24"	20"	18"	1 1/4", 1 1/2", 2", 3"
36"	40"	1/4"	38 1/2"	30"	22"	20"	1 1/4", 1 1/2", 2", 3"
42"	48"	1/4"	44 1/2"	36"	24"	22"	1 1/4", 1 1/2", 2", 3", 4"
48"	54"	1/4"	51"	40"	30"	28"	1 1/4", 1 1/2", 2", 3", 4"



STEELE PLASTICS, LLC
 1280 Sturgis Road
 Conway, AR 72034
 (501) 327-5122 Fax (501) 327-0807

TITLE		SINGLE DOOR STEEL HATCH COVER	
PROJECT		JOB NO.	
		P.O. NO.	
CUSTOMER		DWG. NO.	CVSHTHSD